

Wall-Mount PC 800

Powerful, Compact, Wall-mountable Controllers



A complete computer in a small compact form-factor. It's perfect for firewalls, print servers, automated control boxes or home automation systems. This computer has a 300 MHz processor, and can be equipped with 128 MB RAM and a standard 2.5" notebook hard drive. It has a full complement of standard PC connections which include, serial (2), parallel, and a USB port, and an additional 8-bit PCMCIA TypeI/II/III slot. This system also features a complete integrated audio system and 10/100 Network adapter.

Mainboard & Chipset

Mainboard NS Geode GXL V/GX1

CPU

Embedded Geode GXL 300Mhz, Low Power Processor Onboard.

Front Side Bus

66 MHz FSB

Memory

One 144-pin SO-DIMM, Maximum 128 MB SDRAM

Video

Integrated CS5530 Graphics Chip with Shared Memory Up to 4 MB SDRAM Display Cache

Audio

Integrated Software Audio

Network

Integrated Realtek RTL8139 10/100 Mbps Ethernet

Form Factor

Proprietary

Power Supply

55 Watt (100-240V AC)

Front Panel

USB x2, Mic-In, Line-In, Speaker-out, Serial x2, Parallel x1, Standard VGA x1, PS/2 Keyboard/Mouse, Type II PCMCIA

Device Bays

1x 8-bit PCMCIA Type I/II/III socket (external), 2x 2.5" HDD Bays (internal)

Dimension

Height 3.89" x Width 11" x Depth 5.71"

BIOS

Award PnP Flash BIOS

Operating Systems

Windows 98 Second Edition is standard. Other OS options include: Windows NT 4.0 with Service Pack 6, Windows 2000 Professional, and Windows NT Server

Operating Environment

Temperature 0~60 C°
Relative Humidity 5~95% (non-condensing)

Call your NEX Sales Rep at 480-838-0287

7307 S. Harl Ave., Suite 5 Tempe, Arizona 85283 480-838-0287 fax 480-838-1067 www.nexedge.com

Copyright 2003 NEX, Inc. All rights reserved